

FAN, BLOWER ASSY FOR AIR HANDLING UNIT, BUILT UP BLOWER ASSEMBLY WITH A WELDED FRAME, PILLOW BLOCK BEARINGS, BELT, SHEAVES, CANVAS AND ISOLATORS UNIT SERIAL #S22514-MUA-1, LM-2K-O, SHAFT SIZE: 3/4", BLOWER PULLEY: BK40H, W/O MOTOR

ВЕНТИЛЯТОР, В СБОРЕ ДЛЯ СИСТЕМЫ ВЕНТИЛЯЦИИ И КОНДИЦИОНИРОВАНИЯ. В КОМПЛЕКТЕ С РАМОЙ, ПОДШИПНИКАМИ, ШКИВОМ, РЕМНЕМ И РУКАВОМ, СЕРИЙНЫЙ НОМЕР УЗЛА: S22514-MUA-1, LM-2K-O, ДИАМЕТР ВАЛА: 3/4", ШКИВ ВОЗДУХОДУВКИ: BK40H, БЕЗ ДВИГАТЕЛЯ

*EXAMPLE OF THE VIEW



Eng A ENGINEERED AIR		OCTOBER - 05 - 1995	
DIVISION OF AIRTEX MANUFACTURING PARTNERSHIP 1401 HASTINGS CRESCENT S.E. CALGARY, ALBERTA 1175 TWINNEY CRESCENT, NEWMARKET, ONTARIO			
AIR HANDLING UNIT HEATING UNIT FOR INSTALLATION AT - 40 F OUTDOOR MINIMUM AMBIENT TEMP			
MODEL	LM-2-K-O	SERIAL NUMBER	S22514-MUA-1
SUPPLY CAPACITY	2250	CFM	EXTERNAL S.P. 1.0 "W.C.
FAN SIZE	979		
BLOWER PULLEY	BK40H	R.P.M.	2250
SUPPLY MOTOR PULLEY	1VP62	BELTS	B 36
UNIT ELECTRICAL SPECIFICATIONS			
CIRCUIT #1	380	VOLTS	3 PHASE, 50 Hz
CIRCUIT #1 FEEDER	114.6	AMPS	MAXIMUM FUSE (DUAL ELEMENT) 150 AMPS
CIRCUIT BREAKER	150	AMPS	
SUPPLY FAN MOTOR	3.8	FLA	2.0 HP
ELECTRIC HEAT	109.5	AMPS	72 KW
ELECTRIC HEAT SECTION			
1 STAGES	1.92	KW	1 STAGES 3.84 KW 2 STAGES 7.68 KW
3 STAGES	7.68	KW	
TEMPERATURE RISE 168 °F			
MINIMUM CLEARANCES TO COMBUSTIBLES AND SERVICES			
FRONT	TOP	BOTTOM	SIDE SERVICE SIDE BACK
1"	1"	0"	1" UNIT WIDTH + 10" 1"